



02P: Clasp on the right  
from this view

ITEM	NAME OF PART	MATERIAL	NOTES
6	Screw 2	Steel	M2.5/Zn Plated
5	Screw 1	Steel	M3/Zn Plated
4	Cage	Copper alloy	M3/Ni Plated
3	Clamp	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

  

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/15	/	300/10
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污染等级/ Pollution Degree	III/3	II/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	320/18	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	4	/
螺栓扭矩/Torque Tightening(N·m/Lb.in)	M3: 0.6/5.30		
导线范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	1.0~2.5/28~12		
间距/Pitch(mm)/线数范围/Poles	5.08 N=02~22P		
导线长度/Stripping length(mm)	7		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: SURFACE:

MAT NO.:  
STATUS:  
APPD:  
CHKD:  
DRT:

NAME:  
ZESAKAM-5.08-XXP-1Y-1000A(H)



DRAWING NO.:  
SCALE:  
SHEET 1/1

公差/General	tolerances(mm)
0	>3
2	>6
3	~10
6	~18
10	~30
18	~50
30	~80
50	~120
80	~180
120	~250
180	~315
250	~400
315	~500
400	~500
500	>500

0.1/10	±Z
--------	----